



Test Report : SMA01L-12

1W DC-DC Unregulated Single Output Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2%~+2% (Max)	I/P:5VDC O/P:100% LOAD Ta:25°C	-0.47%	P
2	RIPPLE & NOISE	100mVp-p (Max)	I/P:5VDC O/P:FULL LOAD Ta:25°C	34mV	P
3	LINE REGULATION	-12%~+12% (Max)	I/P:4.5VDC-5.5VDC O/P:FULL LOAD Ta:25°C	-11.27% ~ +10.48%	P
4	LOAD REGULATION	-8.0%~+8.0% (Max)	I/P:5VDC O/P:MIN-FULL LOAD Ta:25°C	-3.31% ~ +2.39%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	78% (Typ)	I/P:5VDC O/P:FULL LOAD Ta:25°C	79.31%	P
2	DC CURRENT	265 mA / FULL LOAD (Max) 32 mA / NO LOAD (Max)	I/P:5VDC O/P:NO / FULL LOAD Ta:25°C	253 mA / FULL LOAD 26 mA / NO LOAD	P

■ SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST
ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT									
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 6HRS I/P:5VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 16HRS I/P:5VDC O/P:FULL LOAD Ta=85°C			P									
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>CENTER</td> <td>45.0°C</td> <td>102.6°C</td> </tr> </tbody> </table>				NO	Position	P/N	1	2	1	CASE	CENTER	45.0°C
NO	Position	P/N	1	2										
1	CASE	CENTER	45.0°C	102.6°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 3 HOURS	I/P:5VDC O/P: 100% LOAD Ta= -40°C	TEST : OK	P									

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2009.9.5	PRODUCT SAMPLE	PASS	PETER	VINCENT ZENG